

**F-95M OM**  
**PTFE STAINLESS STEEL**  
**BRAIDED - HEAVY DUTY**  
**FDA US PHARMACOPEIA**  
**CLASS VI**



<b>TUBE</b>	SMOOTH PTFE - HIGH MECHANICAL AND VIBRATION RESISTANCE, LOW PERMEABILITY, DIELECTRICAL , FIRE RESISTANT, FOOD GRADE (FDA, DVGW, BGA APPROVED). CHEMICALLY INERT, NON STICKING, OZONE AND WEATHER RESISTANT.
<b>REINFORCEMENT</b>	HIGH TENSILE STAINLESS STEEL BRAID AISI 304
<b>APPLICATION</b>	COMPRESSED AIR, GAS, STEAM, FUEL, OIL, CHEMICAL, FOOD AND PHARMACEUTICAL PRODUCTS. PARTICULARLY SUITABLE FOR STEAM PIPING ON INJECTION MOULDING MACHINES, DIATHERMIC OIL INSTALLATIONS, CHARGING LINES FOR CRIOGENIC GASES, COMPRESSOR DISCHARGE LINES, AUTOMOTIVE, PHARMACEUTICAL AND FOOD SECTORS. SOLVENTS, PIGMENTS AND PAINT TRANSFER LINES. HYDRAULIC LINES IN POWER STEERING MARINE APPLICATIONS. NOT SUITABLE FOR MOLTEN ALKALI METALS AND HALOGENS AT ELEVATED TEMPERATURE.
<b>TEMPERATURE</b>	-60°C +260°C (-76°F +500°F)
<b>BRAND TYPE</b>	UNBRANDED
<b>SAFETY FACTOR</b>	4:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	BR mm	BR inch
95MOM003000000	3	1/8	6	0,9	70	2754	125	35	1,38
95MOM005000000	5	3/16	8	1,5	90	2003	3000	63	2,48
95MOM006000000	6	1/4	9	1,5	110	1702	550	76	2,99
95MOM008000000	8	5/16	11	1,65	150	1502	250102		4,02
95MOM01000000010		3/8	13	1,65	170	1301	950127		5,00
95MOM01100000011		13/32	14	0,9	190	1301	950133		5,2
95MOM01300000013		1/2	16	1,65	250	1201	800152		5,98
95MOM01600000016		5/8	19	1,65	300	80	1200178		7,01
95MOM01900000019		3/4	23	1,75	370	80	1200203		7,99
95MOM02200000022		7/8	26	1	410	70	1050250		9,84
95MOM02500000025		1	29	2	510	60	900	3051	2,01

**F-95S OM**  
**PTFE STAINLESS STEEL**  
**BRAIDED - STANDARD DUTY**  
**FDA US PHARMACOPEIA**  
**CLASS VI**



<b>TUBE</b>	SMOOTH PTFE - HIGH MECHANICAL AND VIBRATION RESISTANCE, LOW PERMEABILITY, DIELECTRICAL , FIRE RESISTANT, FOOD GRADE (FDA, DVGW, BGA APPROVED). CHEMICALLY INERT, NON STICKING, OZONE AND WEATHER RESISTANT.
<b>REINFORCEMENT</b>	HIGH TENSILE STAINLESS STEEL BRAID AISI 304
<b>APPLICATION</b>	COMPRESSED AIR, GAS, STEAM, FUEL, OIL, CHEMICAL, FOOD AND PHARMACEUTICAL PRODUCTS. PARTICULARLY SUITABLE FOR STEAM PIPING ON INJECTION MOULDING MACHINES, DIATHERMIC OIL INSTALLATIONS, CHARGING LINES FOR CRIOGENIC GASES, COMPRESSOR DISCHARGE LINES, AUTOMOTIVE, PHARMACEUTICAL AND FOOD SECTORS. SOLVENTS, PIGMENTS AND PAINT TRANSFER LINES. HYDRAULIC LINES IN POWER STEERING MARINE APPLICATIONS. NOT SUITABLE FOR MOLTEN ALKALI METALS AND HALOGENS AT ELEVATED TEMPERATURE.
<b>TEMPERATURE</b>	-60°C +260°C (-76°F +500°F)
<b>BRAND TYPE</b>	UNBRANDED
<b>SAFETY FACTOR</b>	4:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	BR mm	BR inch
95SOM005000000	5	3/16	8	1,3	70	2003000	63	2,48	
95SOM006000000	6	1/4	9	1,3	90	1702550	76	2,99	
95SOM008000000	8	5/16	11	1,45	130	1502250102		4,02	
95SOM010000000	10	3/8	13	1,45	150	1301950127		5,00	
95SOM011000000	11	13/32	13	0,7	160	1301950133		5,24	
95SOM013000000	13	1/2	16	1,5	230	1201800152		5,98	
95SOM016000000	16	5/8	19	1,6	270	80	1200178	7,01	
95SOM019000000	19	3/4	22	1,6	330	80	1200203	7,99	
95SOM022000000	22	7/8	25	0,8	321	70	1050250	9,84	
95SOM025000000	25	1	29	1,95	460	60	900	30512,01	
95SOM028000000	28	1 1/8	32	0,9	525	55	825	30011,81	