

F-95C OM
CONVOLUTED PTFE -
STAINLESS STEEL BRAIDED
FDA US PHARMACOPEIA
CLASS VI



TUBE	CONVOLUTED PTFE - HIGH MECHANICAL AND VIBRATION RESISTANCE, LOW PERMEABILITY, DIELECTRICAL, FIRE RESISTANT, FOOD GRADE (FDA, DVGW, BGA APPROVED). CHEMICALLY INERT, NON STICKING, OZONE AND WEATHER RESISTANT.
REINFORCEMENT	HIGH TENSILE STAINLESS STEEL BRAID AISI 304
APPLICATION	COMPRESSED AIR, GAS, STEAM, FUEL, OIL, CHEMICAL, FOOD AND PHARMACEUTICAL PRODUCTS. PARTICULARLY SUITABLE FOR STEAM PIPING ON INJECTION MOULDING MACHINES, DIATHERMIC OIL INSTALLATIONS, CHARGING LINES FOR CRYOGENIC GASES, COMPRESSOR DISCHARGE LINES, AUTOMOTIVE, PHARMACEUTICAL AND FOOD SECTORS. SOLVENTS, PIGMENTS AND PAINT TRANSFER LINES. HYDRAULIC LINES IN POWER STEERING MARINE APPLICATIONS. NOT SUITABLE FOR MOLTEN ALKALI METALS AND HALOGENS AT ELEVATED TEMPERATURE.
TEMPERATURE	-60°C +260°C (-76°F +500°F)
BRAND TYPE	UNBRANDED
SAFETY FACTOR	4:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	BR mm	BR inch
95COM010000000	10	3/8	16	3	220	100	1500	25	0,98
95COM013000000	13	1/2	19	3	280	75	1125	32	1,26
95COM016000000	16	5/8	22	3,15	330	60	900	51	2,01
95COM019000000	19	3/4	27	3,75	400	50	750	63	2,48
95COM025000000	25	1	33	3,3	550	35	525	102	4,02
95COM032000000	32	1 1/4	39	3,5	750	25	375	127	5,00
95COM038000000	38	1 1/2	46	3,5	860	20	300	152	5,98
95COM051000000	51	2	60	4,6	1180	20	300	203	7,99
95COM076000000	76	3	95	9,5	1700	20	300	310	12,2
95COM102000000	102	4	126	12	4000	15	225	380	14,96